Category: Power suplies
Productname: SZ-400DR
Package: OEM, packed by ten pieces

General information	
Case dimension	150 x 141 x 84 mm
Packing dimension	Packed by 10
Certificate	CE, FCC, ROHS
Features	
Fan speed control	No
Fan	12 cm
Maximum power	400 W
Efficiency	75 %
Protection	Over Load / Over Voltage / Short Circuit
MTBF	>100K hours at 70% of full rated load 25°C ambient
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage **Maximum** **Minimum**	+3.3V + 5V + 12V - 5V - 12V + 5VSB 25A 32A 15A 0.5A 0.5A 2.0A 0.3A 0.3A 1.0A 0A 0A 0A
Inrush Current	50A (PEAK) for 230 Vac
Power connector	1x(20+4 pin),3xMolex,1xFDD,1xP4,1xSATA
Power cord	Yes
Passive PFC	No
Version	2.03
Pallet characteristics	
Pieces per pallet	400 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 1,90 m
Weight per pallet	436 kg

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: SZ-400R
Package: OEM, packed by ten pieces

General information	
Case dimension	150 x 141 x 84 mm
Packing dimension	Packed by 10
Certificate	CE, FCC, ROHS
Features	
Fan speed control	No
Fan	8 cm
Maximum power	400 W
Efficiency	75 %
Protection	Over Load / Over Voltage / Short Circuit
MTBF	>100K hours at 70% of full rated load 25°C ambient
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage **Maximum** **Minimum**	+3.3V + 5V + 12V - 5V - 12V + 5VSB 25A 32A 15A 0.5A 0.5A 2.0A 0.3A 0.3A 1.0A 0A 0A 0A
Inrush Current	50A (PEAK) for 230 Vac
Power connector	1x(20+4 pin),3xMolex,1xFDD,1xP4,1xSATA
Power cord	Yes
Passive PFC	No
Version	2.03
Pallet characteristics	
Pieces per pallet	400 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 1,90 m
Weight per pallet	436 kg

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: SZ-400PR (Rapcon)
Package: OEM, packed by ten pieces

General information	
Case dimension	149 x 140 x 86 mm
Packing dimension	Packed by 10
Certificate	CE, FCC, ROHS
Features	
Fan speed control	No
Fan	8 cm
Maximum power	400 W
Efficiency	75 %
Protection	Over Load / Over Voltage / Short Circuit
MTBF	>100K hours at 70% of full rated load 25°C ambient
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage **Maximum** **Minimum**	+3.3V + 5V + 12V - 5V - 12V + 5VSB 25A 32A 15A 0.5A 0.5A 2.0A 0.3A 0.3A 1.0A 0A 0A 0A
Inrush Current	50A (PEAK) for 230 Vac
Power connector	20+4 pin,3xMolex,1xFDD,1xP4,1xSATA
Power cord	Yes
Passive PFC	Yes
Version	2.03
Pallet characteristics	
Pieces per pallet	400 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 1,90 m
Weight per pallet	436 kg

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: SZ-430PDR
Package: OEM, packed separate

General information	
Case dimension	150 x 141 x 86 mm
Packing dimension	230 x 100 x 65 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Fan speed control	No
Fan	12 cm
Maximum power	430 W
Efficiency	75 %
Protection	Over Load / Over Voltage / Short Circuit
Noise level	Under 25 dB
MTBF	>100K hours at 70% of full rated load 25°C ambient
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage	+3.3V + 5V + 12V - 5V - 12V + 5VSB
Maximum	30A 34A 15A 0.5A 0.5A 2.0A
Minimum	0.3A 0.3A 1.0A 0A 0A 0A
Inrush Current	50A (PEAK) for 230 Vac
Power connector	1x(20+4 pin),4xMolex,1xFDD,1xP4,1xSATA,1xPCI-E
Power cord	Yes
Passive PFC	Yes
Version	2.03
Pallet characteristics	
Pieces per pallet	400 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 1,85 m
Weight per pallet	660 kg

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: USP-3430
Package: Retail

General information	
Case dimension	150 x 140 x 86 mm
Packing dimension	220 x 198 x 95 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Fan speed	Control function inside
Fan	12 cm silent fan
Maximum power	430 W
Efficiency	75 % at full load
Protection	Over Load / Over Voltage / Short Circuit
Noise level	Under 20-25 dB
MTBF	>100K hours at 70% of full rated load
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage	+3.3V + 5V + 12V - 12V + 5VSB
Maximum	26A 38A 22A 0.8A 2.0A
Colour	ORANGE RED YELLOW BLUE PURPLE
Hold-up Time	16.6 ms at full load & normal input voltage
Inrush Current	75A(PEAK) for 115 Vac/150A(PEAK) FOR 230 VAC
Power connector	1x 20+4 pin(sleaved),4xMolex,1xFDD,1xP4,2xSATA, 1xPCI-E
Power cord	Yes
Passive PFC	Yes
Version	2.03
Pallet characteristics	
Pieces per pallet	350 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 2.10 m
Weight per pallet	660 kg

Material: black nickel-plate

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: USP-5550
Package: Retail

General information	
Case dimension	150 x 140 x 95 mm
Packing dimension	220 x 198 x 95 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Fan speed	Control function inside
Fan	12 cm fan for super low noise
Maximum power	550 W
Efficiency	75 % at full load
Protection	Over Load / Over Voltage / Short Circuit
Noise level	Under 20-25 dB
MTBF	>100K hours at 70% of full rated load
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage **Maximum** **Colour**	+3.3V + 5V + 12V - 12V + 5VSB 32A 40A 24A 0.8A 2.5A ORANGE RED YELLOW BLUE PURPLE
Hold-up Time	16.6 ms at full load & normal input voltage
Inrush Current	75A(PEAK) for 115 Vac/150A(PEAK) FOR 230 VAC
Power connector	20+4 pin(sleave cable),4xMolex,1xFDD,1xP4,2xSATA SLI support, Choise: or 2x PCI-E or 1xPCI-E + 8 pin(6+2)
Extra	Passive PFC and Powercord
Version	1.3
Pallet characteristics	
Pieces per pallet	350 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 2.10 m
Weight per pallet	726 kg

Material: black nickel-plate

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: USP-5565
Package: Retail

General information	
Case dimension	140 x 150 x 85 mm
Packing dimension	220 x 198 x 95 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Fan speed	Control function inside
Fan	12 cm fan for ultra low noise
Maximum power	565 W
Efficiency	75 % at full load
Protection	Over Load / Over Voltage / Short Circuit
Noise level	Under 20 dB
MTBF	>100K hours at 70% of full rated load
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage	+3.3V + 5V +12V1 -12V2 -12V + 5VSB
Maximum	35A 35A 20A 20A 0.8A 2.5A
Colour	ORANGE RED YELLOW YELLOW BLUE PURPLE
Hold-up Time	16.6 ms at full load & normal input voltage
Inrush Current	150A(PEAK)FOR 230 VAC
Power connector	20+4 pin,4xMolex,1xFDD,1xP4,2xSATA, SLI support
	Choise: or 2x PCI-E or 1xPCI-E + 8 pin(6+2)
Extra	Passive PFC and Powercord
Version	2.2
Pallet characteristics	
Pieces per pallet	350 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 1,70 m
Weight per pallet	525 kg

Material: black nickel-plate

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: USP-5580
Package: Retail

General information	
Case dimension	158 x 140 x 86 mm
Packing dimension	200 x 222 x 95 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Fan speed	Control function inside
Fan	14 cm fan for ultra low noise
Maximum power	580 W
Efficiency	75 % at full load
Protection	Over Load / Over Voltage / Short Circuit
Noise level	Low acoustic noise under 20 dB
MTBF	>100K hours at 70% of full rated load
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage **Maximum**	+3.3V + 5V +12V -12V + 5VSB 32A 35A 30A 0.8A 2.5A
Colour	ORANGE RED YELLOW BLUE PURPLE
Hold-up Time	16.6 ms at full load & normal input voltage
Inrush Current	75A(PEAK) for 115 Vac/150A(PEAK) FOR 230 VAC
Power connector	1x20+4 pin, 4xMolex,2xFDD,1xP8pin,4xSATA, Choise: or 2x PCI-E or 1xPCI-E + 8 pin(6+2),Passive PFC, SLI support, all sleeve cables and powercord
Version	1.3
Pallet characteristics	
Pieces per pallet	350 pieces / 10 pieces per carton
Measurements pallet	1,00 x1,20 x 1,70 m
Weight per pallet	775 kg

Material: black nickel-plate

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: USP-7600
Package: Retail

General information	
Case dimension	150 X 156 X 86 mm
Packing dimension	280 x 180x 96 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Operating temperature	Operating temp: +10 C~+50 C
Fan	14 cm fan with ball bearing cooling fan
Maximum power	600 W
Humidity	5-95% RH
Power Good Signal	On Delay 100-500ms, off Delay 1 ms
Efficiency	82 %
Hold-up Time	16.6 ms at full load & normal input voltage
Comply with	ATX12V and EPS12V ,V2.91
MTBF	>100K hours at 82% of full rated load
Supports: Vista operating system with High-End Graphic card, Provides high +12V current capability. SLI ready and support Intel&AMD Dual & Multi core	
Specifications	
Protection circuit	OCP, OVP, UVP, OLP, SCP,+line input fuse protection
Output voltage **Maximum (600W)** **Regulation**	+3.3V + 5V +12V1 -12V2 -12V + 5VSB 28A 25A 20A 25A 0.5A 2.5A +5% +5% +5% +5% +5% +5%
Inrush Current	75A(PEAK) for 115 Vac/150A(PEAK) FOR 230 VAC
Power connector	1x20+4 pin, 4xMolex,1xFDD,4xSATA,(2xPCI-E,or 1x 6+2pin and 1x PCI-E), (1x8 pin(4+4), or 2x 4 pin) All cables sleaved. 1x Powercord
PFC	Active PFC
Version	2.31

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com

Category: Power suplies
Productname: USP-7630
Package: Retail

Material: black nickel-plate

General information	
Case dimension	150 X 140 X 86 mm
Packing dimension	300 x 230 x 95 mm
Certificate	CE, FCC, ROHS, TUV
Features	
Fan speed	Control function inside
Fan	12 cm fan with intelligent speed control
Maximum power	630 W
Efficiency	80 % under wide load range (30%-100%)
Protection	Over Load/Over Voltage/Short Circuit/EMI shielding
MTBF	>100K hours at 70% of full rated load
Applications: Intel Pentium 4, Intel Celeron D, Intel Core 2, Intel core 2 Duo, Intel Core 2 Extreme, Intel Quad core, AMD Athlon 64 X2, AMD Athlon 64, etc.	
Specifications	
Operating temperature	Operating temp: +10 C~+50 C
Output voltage **Maximum** **Colour**	+3.3V + 5V +12V1 -12V2 -12V + 5VSB 30A 40A 20A 20A 0.5A 2.5A ORANGE RED YELLOW YELLOW BLUE PURPLE
Hold-up Time	16.6 ms at full load & normal input voltage
Inrush Current	75A(PEAK) for 115 Vac/150A(PEAK) FOR 230 VAC
Power connector	1x20+4 pin, 4xMolex,2xFDD,1xSATA,2xPCI-E, 1x8 pin(4+4), SLI support, DUAL+12V, Active PFC, Detachable sleeve cables and Powercord
Version	1.3
Pallet characteristics	
Pieces per pallet	280 pieces / 5 pieces per carton
Measurements pallet	1,00 x1,20 x 1,85 m
Weight per pallet	725 kg

HKC Europe BV
Bijsterhuizen 3007G
Tel:0031(024)3434231
Fax: 0031 (O)24 3442373
Http://www.HKC-Europe.com
E-mail:John@hkc-europe.com